

European Technical Approval**ETA 13/0304****Trade name**

1. 3M™ High Intensity Prismatic Reflective Sheeting Series 3930 printed with 3M™ process colour series 4700 + 3M™ Premium Protective Overlay Film 1160
2. 3M™ High Intensity Prismatic Reflective Sheeting Series 3930 + 3M™ Piezo Inkjet Ink Series 8800UV + 3M™ Premium Protective Overlay Film 1160
3. 3M™ High Intensity Prismatic Reflective Sheeting Series 3930 + 3M™ Dew Resistant Overlay Film 1180
4. 3M™ High Intensity Prismatic Reflective Sheeting Series 3930 + 3M™ Electrocut Film Series 1170 + 3M™ Dew Resistant Overlay Film 1180

Approval holder

3M Deutschland GmbH
Carl-Schurz-Str. 1
D- 41453 Neuss, Germany

Website

www.3m.com

Generic type and use of construction system

Micro-prismatic retro-reflective sheeting for traffic signs

Validity : from :

2013-06-27

To :

2018-06-26

Manufacturing plant(s) :

3M Deutschland GmbH Plant Hilden,
Düsseldorferstr. 121-125, D-40705 Hilden,
Germany

3M Brownwood, Texas 76801 - US

This ETA contains :

22 pages including 1 annex which forms an integral part of the document.



European Organisation for Technical Approvals
Organisation Européenne pour l'Agrément Technique
Europäische Organisation für Technische Zulassungen

I. Legal bases and general conditions

- 1 This European Technical Approval is issued by UBAtc (Union belge pour l'Agrément technique de la construction, i.e. Belgian Union for technical Approval in construction), in accordance with:
 - Council Directive 89/106/EEC of 21 December 1988 (CPD) on the approximation of laws, regulations and administrative provisions of Member States relating to construction products¹, modified by the Council Directive 93/68/EEC² and regulation (EC) N° 1882/2003 of the European Parliament and of the Council³
 - Belgian implementation of CPD according to the law of 25th of March 1996, coming into force on 11 September 1998⁴
 - Common Procedural Rules for Requesting, Preparing and the Granting of European technical approvals set out in the Annex of Commission Decision 94/23/EC⁵.
- 2 UBAtc is authorized to check whether the provisions of this European Technical Approval are met. Checking may take place in the manufacturing plant. Nevertheless, the responsibility for the conformity of the products to the European Technical Approval and their suitability for the intended use remains with the holder of the European Technical Approval.
- 3 This European Technical Approval is not to be transferred to other manufacturers, agents of manufacturers, or manufacturing plants other than those indicated on page 1 of this European Technical Approval.
- 4 This European Technical Approval may be withdrawn by UBAtc, in particular pursuant to information by the Commission according to article 5(1) of Council Directive 89/106/EEC.
- 5 Reproduction of this European Technical Approval including transmission by electronic means shall be in full. However, partial reproduction can be made with the written consent of UBAtc. In this case partial reproduction has to be designated as such. Texts and drawings of advertising brochures shall not contradict or misuse the European Technical Approval.
- 6 Subject to the application introduced, the European Technical Approval is issued by the approval body in its official languages. These versions correspond fully to the English version circulated in EOTA. Translations into other languages have to be designated as such.
- 7 The ETA holder confirms to guarantee that the product(-s) to which this approval relates, is/are produced and marketed in accordance with and comply with all applicable legal and regulatory provisions, including, without limitation, national and European legislation on the safety of products and services. The ETA-holder shall notify the UBAtc immediately in writing of any circumstance affecting the aforementioned guarantee. This approval is issued under the condition that the aforementioned guarantee by the ETA holder is continuously observed.
- 8 This ETA includes components that are already covered by 11/0426, with new combinations from the existing 'toolkit' of inks, overlay etc.

¹ Official Journal of the European Communities L40, 11.2.1989, p.12

² Official Journal of the European Communities L220, 30.08.1993, p.1

³ Official Journal of the European Communities L284, 31.10.2003, p.1

⁴ Arrêté royal concernant les produits de construction (19 août 1998, décision ministérielle du 11 septembre 1998)

⁵ Official Journal of the European Communities L17, 20.01.1994, p.34

II. SPECIFIC CONDITIONS OF THE EUROPEAN TECHNICAL APPROVAL (ETA)

1. Definition and scope of product and intended use

1.1 General

The product consists of a micro-prismatic retro-reflective sheeting made of optical prismatic lenses elements formed in a transparent synthetic resin, sealed and backed with a pressure sensitive adhesive to form a durable bond to the sign substrates. The sheeting has a smooth surface with a distinctive interlocking seal pattern and may or may not have orientation marks, visible from the face.

The product is supplied in the combinations listed here.

ETA 11/0426 and 11/0427 cover additional combinations of 3M™ High Intensity Prismatic Reflective Sheeting series 3930 with various overlay films and process colours.

1.2 Components

An overview of the complete set of components of "3M™ High Intensity Prismatic Reflective Sheeting series 3930", and combinations with or without "3M™ Electrocut Film series 1170" or "Process Colour Series 4700 or Piezo Inkjet Ink Series 8800 UV", and with or without 3M™ Dew Resistant Overlay Film 1180 or 3M™ Premium Protective Overlay Film 1160 is presented in Table 1.

This ETA contains ;

Initial performance and performance after accelerated artificial weathering

Use option 1, see Annex 1

1. 3M™ High Intensity Prismatic Reflective Sheeting Series 3930 printed with 3M™ process colour series 4700 + 3M™ Premium Protective Overlay Film 1160
 2. 3M™ High Intensity Prismatic Reflective Sheeting Series 3930 + 3M™ Piezo Inkjet Ink Series 8800UV + 3M™ Premium Protective Overlay Film 1160
 3. 3M™ High Intensity Prismatic Reflective Sheeting Series 3930 + 3M™ Dew Resistant Overlay Film 1180
 4. 3M™ High Intensity Prismatic Reflective Sheeting Series 3930 + 3M™ Electrocut Film Series 1170 + 3M™ Dew Resistant Overlay Film 1180
-

Components	Trade name	Colours/code	Characteristics	
Micro-prismatic retro-reflective sheeting	3M™ High Intensity Prismatic Reflective Sheeting Series 3930	White	3930	Thickness: 0,32 - 0,49 mm Rolls in various lengths and widths
		Red	3932	
		Yellow	3931	
		Blue	3935	
Overlay film	3M™ ELECTROCUT FILM series 1170	Yellow	1171	Combined Thickness: 0,549 mm Rolls in various length and widths
		Red	1172	
		Blue	1175	
		Green	1177	
		Brown	1179	
Process colour	3M™ Process Colour Series 4700	Yellow	4714	20-25 m²/l
		Red	4701	
		Blue	4710	
		Green	4718	
Process colour for digital printing	Piezo Inkjet Ink Series 8800 UV	Yellow		18-20ml/m²
		Red		
		Blue		
		Green		
		Brown		
	3M™ Premium Protective Overlay Film 1160 (anti-graffiti)			Combined Thickness: 0,549 mm Rolls in various length and widths
	3M™ Dew resistant overlay film 1180			Combined Thickness: 0,549 mm Rolls in various length and widths

Table 1: Components of the product

1.3 Intended use

The construction product is used to manufacture sign faces for traffic signs. The intended use includes, for example:

- retro-reflective signs, retro-reflective and trans-illuminated signs (See also EN 12899-1)
- trans-illuminated traffic bollards (See also EN 12899-2)
- fixed retroreflector for road delineators (See also EN 12899-3)
- variable message signs (See also EN 12966)

The intended use excludes road-markings as defined in EN 1436. The assumed intended working life of the product is 10 years provided that it is subjected to appropriate use and maintenance. The indications given as to the working life of the product cannot be interpreted as a guarantee given by the Manufacturer or by the Approval Body.

2. Characteristics of product(s) and methods of verification

2.1 General

The identification tests and the assessment of fitness for use for the products listed in chapter 1.1 were carried out according to the verification methods in clause 3 of this ETA.

The ETA is issued for the product on the basis of information/data deposited at UBAtc which identify the product that was assessed and judged. Changes to the production process of the product or to its components which could result in deposited information/data being incorrect, shall be notified to UBAtc before they are introduced and UBAtc will assess whether or not such changes affect the ETA and, if so, whether further assessment and/or modification to the ETA shall be necessary.

The characteristics of the product not mentioned in this ETA nor in the annexes shall correspond to the respective values laid down in the Technical Documentation of this ETA, checked by UBAtc. Details of test results are included in the related Evaluation Report.

2.2 Characteristics of the product

2.2.1 Hygiene, health and the environment

2.2.1.1 Release of dangerous substances

The product complies with the provisions of Guidance Paper H ("A harmonized approach relating to Dangerous substances under the construction products directive", Edition 2002) about dangerous substances.

Colours		Chromaticity Coordinates				Pass/fail	Luminance Factor β
		1	2	3	4		Class
Yellow on white	x	0.494	0.470	0.513	0.545	Pass	B2
	y	0.505	0.480	0.437	0.454		≥ 0.24
Red on White	x	0.735	0.700	0.610	0.660	Pass	B2
	y	0.265	0.250	0.340	0.340		≥ 0.03
Green on White	x	0.110	0.170	0.170	0.110	Pass	B2
	y	0.415	0.415	0.500	0.500		≥ 0.03
Blue on White	x	0.130	0.160	0.160	0.130	Pass	B2
	y	0.090	0.090	0.140	0.140		≥ 0.01

Table 2: Day-time colour and Luminance Factor

A written declaration of conformity in this respect was made by the manufacturer. In addition to the specific clauses relating to dangerous substances contained in this European Technical Approval, there may be other requirements applicable to the products falling within its scope (e.g. transposed European legislation and national laws, regulations and administrative provisions). In order to meet the provisions of the EU Construction Products Directive, these requirements need also to be complied with, when and where they apply.

2.2.2 Safety in use of "3M High Intensity Prismatic Reflective Sheeting series 3930 printed with "Process Colour series 4700"

2.2.2.1 Visibility of "3M High Intensity Prismatic Reflective Sheeting series 3930 printed with "Process Colour series 4700 + 3M™ Premium Protective Overlay Film 1160"

2.2.2.1.1 Day-time colour and Luminance Factor

The characteristics of Day-time colour and Luminance Factor (see Table 2) have been determined according to clause 3.2.1

2.2.2.1.2 Coefficient of Retro-reflection Case A

The Coefficient of Retro-reflection - Case A (see Table 3) has been determined according to clause 3.2.2. For material processed with process colours, with or without clear overlay film, the minimum value of the coefficient of Retro-reflection shall not be less than 70% of the values specified in the tables.

Colour	Class R2
Yellow on white	pass
Red on White	pass
Green on White	pass
Blue on White	pass

Table 3: Coefficient of retro-reflection Case A

2.2.2.1.3 Rotational symmetry

The rotational symmetry (see Table 4) has been determined according to clause 3.2.3.

Colours	Pass/Fail
Yellow on White	Pass
Red on White	Pass
Blue on White	Pass
Green on White	Pass

Table 4: Rotational symmetry

2.2.2.1.4 Impact resistance

The Impact resistance (see Table 5) has been determined according to clause 3.2.4.

Product	Colour of the sheeting	Colour of the film	Observations after the test
"3M High Intensity Prismatic Reflective Sheeting series 3930" printed with "Process Colour Series 4700 + 3M™ Premium Protective Overlay Film 1160"	White 3930	Yellow Red Blue Green	Pass: no cracking has been observed outside the impact area.

Table 5: Impact resistance

2.2.3 Durability "3M High Intensity Prismatic Reflective Sheeting serie 3930" printed with "Process Colour Series 4700" + "3M™ Premium Protective Overlay Film 1160"

2.2.3.1. Visibility after accelerated artificial weathering of "3M High Intensity Prismatic Reflective Sheeting serie 3930" printed with "Process Colour Series 4700" + "3M™ Premium Protective Overlay Film 1160"

2.2.3.1.1 Day-time colour and Luminance factor (see Table 6) after accelerated artificial weathering of "3M High Intensity Prismatic Reflective Sheeting serie 3930" printed with "Process Colour Series 4700" + "3M™ Premium Protective Overlay Film 1160"

The tests were performed according to clause 3.3

Colours		Chromaticity Coordinates				Luminance Factor β	
		1	2	3	4	Class B1	Class B2
Yellow reference	x	0.545	0.487	0.427	0.465	≥ 0.16	≥ 0.24
	y	0.454	0.423	0.483	0.534		
Yellow on White results		Pass				Class B2	
Red reference	x	0.735	0.674	0.569	0.655	≥ 0.03	≥ 0.03
	y	0.265	0.236	0.341	0.345		
Red on White results		Pass				Class B2	
Green reference	x	0.007	0.248	0.177	0.026	≥ 0.03	≥ 0.03
	y	0.703	0.393	0.362	0.399		
Green on White results		Pass				Class B2	
Blue reference	x	0.078	0.150	0.210	0.137	≥ 0.01	≥ 0.01
	y	0.171	0.220	0.160	0.038		
Blue on White results		Pass				Class B2	

Table 6: Day-time colour and Luminance factor

2.2.3.1.2 Coefficient of retro-reflection Case A (see Table 7) after accelerated artificial weathering of "3M High Intensity Prismatic Reflective Sheeting serie 3930" printed with "Process Colour Series 4700" + "3M™ Premium Protective Overlay Film 1160"

The tests were performed according to clause 3.3. The values shall not be less than 80% of the values required for new material under clause 3.2.2, as appropriate.

Colour	Class R2
Yellow	pass
Red	pass
Green	pass
Blue	pass

Table 7: Coefficient of retro-reflection Case A

2.2.4 Safety in use of "3M High Intensity Prismatic Reflective Sheeting series 3930 printed with 3M Piezo Inkjet Ink Series 8800UV + 3M Premium Protective Overlay Film 1160"

2.2.4.1 Visibility of "3M High Intensity Prismatic Reflective Sheeting series 3930 printed with 3M Piezo Inkjet Ink Series 8800UV + 3M Premium Protective Overlay Film 1160"

2.2.4.1.1 Day-time colour and Luminance Factor

The characteristics of Day-time colour and Luminance Factor (see Table 8) have been determined according to clause 3.2.1

Colours		Chromaticity Coordinates				Luminance Factor β	
		1	2	3	4	Class B1	Class B2
White reference	x	0.305	0.335	0.325	0.295	≥ 0.27	≥ 0.40
	y	0.315	0.345	0.355	0.325		
White results		Pass				Class B2	
Yellow reference	x	0.494	0.470	0.513	0.545	≥ 0.16	≥ 0.24
	y	0.505	0.480	0.437	0.454		
Yellow on White results		Pass				Class B2	
Red reference	x	0.735	0.700	0.610	0.660	≥ 0.03	≥ 0.03
	y	0.265	0.250	0.340	0.340		
Red on White results		Pass				Class B2	
Green reference	x	0.110	0.170	0.170	0.110	≥ 0.03	≥ 0.03
	y	0.415	0.415	0.500	0.500		
Green on White results		Pass				Class B2	
Blue reference	x	0.130	0.160	0.160	0.130	≥ 0.01	≥ 0.01
	y	0.090	0.090	0.140	0.140		
Blue on White results		Pass				Class B2	
Brown reference		0.455	0.523	0.479	0.558	0.04 – 0.06	0.03 – 0.09
		0.397	0.429	0.373	0.394		
Brown on White results		Pass				Class B1 & B2	

Table 8: Day-time colour and Luminance factor

2.2.4.1.2 Coefficient of Retro-reflection Case A

The Coefficient of Retro-reflection - Case A (see Table 9) has been determined according to clause 3.2.2.

Colour	Class R2
White	pass
Yellow on white	pass
Red on White	pass
Green on White	pass
Blue on White	pass
Brown on White	pass

Table 9: Coefficient of retro-reflection Case A

2.2.4.1.3 Rotational symmetry

The rotational symmetry (see Table 10) has been determined according to clause 3.2.3.

Colours	Pass/Fail
White	Pass
Yellow on White	Pass
Red on White	Pass
Blue on White	Pass
Green on White	Pass
Brown on White	Pass

Table 10: Rotational symmetry

2.2.4.1.4 Impact resistance

The Impact resistance (see Table 11) has been determined according to clause 3.2.4.

Product	Colour of the sheeting	Colour of the film	Observations after the test
"3M High Intensity Prismatic Reflective Sheeting series 3930 printed with 3M Piezo Inkjet Ink Series 8800UV + 3M Premium Protective Overlay Film 1160"	White 3930	Unprinted Yellow Red Blue Green Brown	Pass: no cracking has been observed outside the impact area.

Table 11: Impact resistance

2.2.5 Durability "3M High Intensity Prismatic Reflective Sheeting series 3930 printed with 3M Piezo Inkjet Ink Series 8800UV + 3M Premium Protective Overlay Film 1160"

2.2.5.1 Visibility after accelerated artificial weathering of "3M High Intensity Prismatic Reflective Sheeting series 3930 printed with 3M Piezo Inkjet Ink Series 8800UV + 3M Premium Protective Overlay Film 1160"

2.2.5.1.1. Day-time colour and Luminance factor (see Table 12) after accelerated artificial weathering of "3M High Intensity Prismatic Reflective Sheeting series 3930 printed with 3M Piezo Inkjet Ink Series 8800UV + 3M Premium Protective Overlay Film 1160"

The tests were performed according to clause 3.3

Colours		Chromaticity Coordinates				Luminance Factor β	
		1	2	3	4	Class B1	Class B2
White reference	x	0.355	0.305	0.285	0.335	≥ 0.27	≥ 0.40
	y	0.355	0.305	0.325	0.375		
White results		Pass				Class B2	
Yellow reference	x	0.545	0.487	0.427	0.465	≥ 0.16	≥ 0.24
	y	0.454	0.423	0.483	0.534		
Yellow on White results		Pass				Class B2	
Red reference	x	0.735	0.674	0.569	0.655	≥ 0.03	≥ 0.03
	y	0.265	0.236	0.341	0.345		
Red on White results		Pass				Class B2	
Green reference	x	0.007	0.248	0.177	0.026	≥ 0.03	≥ 0.03
	y	0.703	0.393	0.362	0.399		
Green on White results		Pass				Class B2	
Blue reference	x	0.078	0.150	0.210	0.137	≥ 0.01	≥ 0.01
	y	0.171	0.220	0.160	0.038		
Blue on White results		Pass				Class B2	
Brown reference	x	0.455	0.523	0.479	0.558	0.04 – 0.06	0.03 – 0.09
	y	0.397	0.429	0.373	0.394		
Brown on White results		Pass				Class B1 & B2	

Table 12: Day-time colour and Luminance factor

2.2.5.1.2 Coefficient of retro-reflection Case A (see Table 13) after accelerated artificial weathering test of "3M High Intensity Prismatic Reflective Sheeting Series 3930 + 3M Piezo Inkjet Ink Series 8800UV + 3M Premium Protective Overlay Film 1160"

The tests were performed according to clause 3.3. The values shall not be less than 80% of the values required for new material under clause 3.2.2, as appropriate.

Colour	Class R2
White	pass
Yellow on white	pass
Red on White	pass
Green on White	pass
Blue on White	pass
Brown on White	pass

Table 13: Coefficient of retro-reflection Case A

2.2.6 Safety in use of "3M High Intensity Prismatic Reflective Sheeting series 3930 + 3M Dew Resistant Overlay Film 1180"

2.2.6.1 Visibility of "3M High Intensity Prismatic Reflective Sheeting series 3930 + 3M Dew Resistant Overlay Film 1180"

2.2.6.1.1 Day-time colour and Luminance Factor

The characteristics of Day-time colour and Luminance Factor (see Table 14) have been determined according to clause 3.2.1

Colours		Chromaticity Coordinates				Luminance Factor β	
		1	2	3	4	Class B1	Class B2
White reference	x	0.305	0.335	0.325	0.295	≥ 0.27	≥ 0.40
	y	0.315	0.345	0.355	0.325		
White results	x	Pass				Class B2	
	y						
Yellow reference	x	0.494	0.470	0.513	0.545	≥ 0.16	≥ 0.24
	y	0.505	0.480	0.437	0.454		
Yellow results	x	Pass				Class B2	
	y						
Red reference	x	0.735	0.700	0.610	0.660	≥ 0.03	≥ 0.03
	y	0.265	0.250	0.340	0.340		
Red results	x	Pass				Class B2	
	y						
Blue reference	x	0.130	0.160	0.160	0.130	≥ 0.01	≥ 0.01
	y	0.090	0.090	0.140	0.140		
Blue results	x	Pass				Class B2	
	y						

Table 14: Day-time colour and Luminance factor

2.2.6.1.2 Coefficient of Retro-reflection Case A

The Coefficient of Retro-reflection - Case A (see Table 15) has been determined according to clause 3.2.2.

Colour	Class R2
White	pass
Yellow	pass
Red	pass
Blue	pass

Table 15: Coefficient of retro-reflection Case A

2.2.6.1.3 Rotational symmetry

The rotational symmetry (see Table 16) has been determined according to clause 3.2.3.

Colours	Pass/Fail
White	Pass
Yellow	Pass
Red	Pass
Blue	Pass

Table 16: Rotational symmetry

2.2.6.1.4 Impact resistance

The Impact resistance (see Table 17) has been determined according to clause 3.2.4.

Product	Colours	Pass/fail
"3M High Intensity Prismatic Reflective Sheeting series 3930 + 3M Dew Resistant Overlay Film 1180"	White	Pass: no cracking has been observed outside the impact area.
	Red	
	Yellow	
	Blue	

Table 17: Impact resistance

2.2.7 Durability of "3M High Intensity Prismatic Reflective Sheeting series 3930 + 3M Dew Resistant Overlay Film 1180"

2.2.7.1 Visibility after accelerated artificial weathering of "3M High Intensity Prismatic Reflective Sheeting series 3930 + 3M Dew Resistant Overlay Film 1180"

2.2.7.1.1. Day-time colour and Luminance factor (see Table 18) after accelerated artificial weathering of "3M High Intensity Prismatic Reflective Sheeting series 3930 + 3M Dew Resistant Overlay Film 1180"

The tests were performed according to clause 3.3.

Colours		Chromaticity Coordinates				Luminance Factor β	
		1	2	3	4	Class B1	Class B2
White reference	x	0.355	0.305	0.285	0.335	≥ 0.27	≥ 0.40
	y	0.355	0.305	0.325	0.375		
White results	x	Pass				Class B2	
	y						
Yellow reference	x	0.545	0.487	0.427	0.465	≥ 0.16	≥ 0.24
	y	0.454	0.423	0.483	0.534		
Yellow results	x	Pass				Class B2	
	y						
Red reference	x	0.735	0.674	0.569	0.655	≥ 0.03	≥ 0.03
	y	0.265	0.236	0.341	0.345		
Red results	x	Pass				Class B2	
	y						
Blue reference	x	0.078	0.150	0.210	0.137	≥ 0.01	≥ 0.01
	y	0.171	0.220	0.160	0.038		
Blue results	x	Pass				Class B2	
	y						

Table 18: Day-time colour and Luminance factor

2.2.7.1.2 Coefficient of retro-reflection Case A (see Table 19) after accelerated artificial weathering test of "3M High Intensity Prismatic Reflective Sheeting Series 3930 + 3M Dew Resistant Overlay Film 1180"

The tests were performed according to clause 3.3. The values shall not be less than 80% of the values required for new material under clause 3.2.2, as appropriate.

Colour	Class R2
White	pass
Yellow	pass
Red	pass
Blue	pass

Table 19: Coefficient of retro-reflection Case A

2.2.8 Safety in use of "3M High Intensity Prismatic Reflective Sheeting series 3930 + 3M Electrocut Film Series 1170 + 3M Dew Resistant Overlay Film 1180"

2.2.8.1 Visibility of "3M High Intensity Prismatic Reflective Sheeting series 3930 + 3M Electrocut Film Series 1170 + 3M Dew Resistant Overlay Film 1180"

2.2.8.1.1 Day-time colour and Luminance Factor

The characteristics of Day-time colour and Luminance Factor (see Table 20) have been determined according to clause 3.2.1

Colours		Chromaticity Coordinates				Luminance Factor β	
		1	2	3	4	Class B1	Class B2
Yellow reference	x	0.494	0.470	0.513	0.545	≥ 0.16	≥ 0.24
	y	0.505	0.480	0.437	0.454		
Yellow results	x	Pass				Class B2	
	y						
Red reference	x	0.735	0.700	0.610	0.660	≥ 0.03	≥ 0.03
	y	0.265	0.250	0.340	0.340		
Red results	x	Pass				Class B2	
	y						
Green reference	x	0.110	0.170	0.170	0.110	≥ 0.03	≥ 0.03
	y	0.415	0.415	0.500	0.500		
Green results	x	Pass				Class B2	
	y						
Blue reference	x	0.130	0.160	0.160	0.130	≥ 0.01	≥ 0.01
	y	0.090	0.090	0.140	0.140		
Blue results	x	Pass				Class B2	
	y						
Brown reference	x	0.455	0.523	0.479	0.558	0.04 – 0.06	0.03 – 0.09
	y	0.397	0.429	0.373	0.394		
Brown results	x	Pass				Class B2	
	y						

Table 20: Day-time colour and Luminance factor

2.2.8.1.2 Coefficient of Retro-reflection Case A

The Coefficient of Retro-reflection - Case A (see Table 21) has been determined according to clause 3.2.2.

Colour	Class R2
Yellow	pass
Red	pass
Green	pass
Blue	pass
Brown	pass

Table 21: Coefficient of retro-reflection Case A

2.2.8.1.3 Rotational symmetry

The rotational symmetry (see Table 22) has been determined according to clause 3.2.3.

Colours	Pass/Fail
Yellow	Pass
Red	Pass
Blue	Pass
Green	Pass
Brown	Pass

Table 22: Rotational symmetry

2.2.8.1.4 Impact resistance

The Impact resistance (see Table 23) has been determined according to clause 3.2.4.

Product	Colours	Pass/fail
"3M High Intensity Prismatic Reflective Sheeting series 3930 + 3M Electrocut Film Series 1170 + 3M Dew Resistant Overlay Film 1180"	Red	Pass: no cracking has been observed outside the impact area.
	Yellow	
	Green	
	Blue	
	Brown	

Table 23: Impact resistance

2.2.9. Durability of "3M High Intensity Prismatic Reflective Sheeting series 3930 + 3M Electrocut Film Series 1170 + 3M Dew Resistant Overlay Film 1180"

2.2.9.1 Visibility after accelerated artificial weathering of "3M High Intensity Prismatic Reflective Sheeting series 3930 + 3M Electrocut Film Series 1170 + 3M Dew Resistant Overlay Film 1180"

2.2.9.1.1 Day-time colour and Luminance factor (see Table 24) after accelerated artificial weathering of "3M High Intensity Prismatic Reflective Sheeting series 3930 + 3M Electrocut Film Series 1170 + 3M Dew Resistant Overlay Film 1180"

The tests were performed according to clause 3.3.

Colours		Chromaticity Coordinates				Luminance Factor B	
		1	2	3	4	Class B1	Class B2
Yellow reference	x	0.545	0.487	0.427	0.465	≥ 0.16	≥ 0.24
	y	0.454	0.423	0.483	0.534		
Yellow results	x	Pass				Class B2	
	y						
Red reference	x	0.735	0.674	0.569	0.655	≥ 0.03	≥ 0.03
	y	0.265	0.236	0.341	0.345		
Red results	x	Pass				Class B2	
	y						
Green reference	x	0.007	0.248	0.177	0.026	≥ 0.03	≥ 0.03
	y	0.703	0.393	0.362	0.399		
Green results	x	Pass				Class B2	
	y						
Blue reference	x	0.078	0.150	0.210	0.137	≥ 0.01	≥ 0.01
	y	0.171	0.220	0.160	0.038		
Blue results	x	Pass				Class B2	
	y						
Brown reference	x	0.455	0.523	0.479	0.558	0.04 – 0.06	0.03 – 0.09
	y	0.397	0.429	0.373	0.394		
Brown results	x	Pass				Class B2	
	y						

Table 24: Day-time colour and Luminance factor

2.2.9.1.2 Coefficient of retro-reflection Case A (see Table 25) after accelerated artificial weathering test of “3M High Intensity Prismatic Reflective Sheeting Series 3930 + 3M Electrocut Film Series 1170 + 3M Dew Resistant Overlay Film 1180”

The tests were performed according to clause 3.3. The values shall not be less than 80% of the values required for new material under clause 3.2.2, as appropriate.

Colour	Class R2
Yellow	pass
Red	pass
Green	pass
Blue	pass
Brown	pass

Table 25: Coefficient of retro-reflection Case A

3. Verification Methods for determining the relevant characteristics of the construction product.

3.1 Hygiene, health and the environment

3.1.1. Release of dangerous substances

The product/kit shall comply with all relevant European and national provisions applicable for the uses for which it is brought to the market. The attention of the applicant should be drawn on the fact that for other uses or other Member States of destination there may be other requirements which would have to be respected.

3.2 Safety in use

3.2.1. Day-time colour and Luminance Factor

The chromaticity coordinates (x, y) and the luminance factor (β) are measured in accordance with CIE Publication 15.2 Colourimetry – 1986 using 45/0 geometry and shall be calculated from the total spectral radiance factors computed for CIE illuminant D65 for the CIE 1931 (2°) standard colorimetric observer.

The position of the sample in the measuring system will be indicated by an orientation mark. The orientation mark has to be adjusted 90° to the incident plane. The incident plane is formed out of the rectangle on the sample surface and the incoming light beam.

The chromaticity coordinates shall be within the colour boxes and the Luminance factor shall comply with values in Table 26.

Colour		Chromaticity Coordinates				Luminance Factor β	
		1	2	3	4	Class B1	Class B2
White	x	0.305	0.335	0.325	0.295	≥ 0.27	≥ 0.40
	y	0.315	0.345	0.355	0.325		
Yellow	x	0.494	0.470	0.513	0.545	≥ 0.16	≥ 0.24
	y	0.505	0.480	0.437	0.454		
Red	x	0.735	0.700	0.610	0.660	≥ 0.03	≥ 0.03
	y	0.265	0.250	0.340	0.340		
Green	x	0.110	0.170	0.170	0.110	≥ 0.03	≥ 0.03
	y	0.415	0.415	0.500	0.500		
Brown	x	0.455	0.523	0.479	0.558	0.04 – 0.06	0.03 – 0.09
	y	0.397	0.429	0.373	0.394		
Blue	x	0.130	0.160	0.160	0.130	≥ 0.01	≥ 0.01
	y	0.090	0.090	0.140	0.140		

Table 26: Permitted colour area in CIE 1931 diagram and Luminance factors for daylight appearance of new materials

3.2.2. Coefficient of Retroreflection

The coefficient of retro-reflection R' is measured in accordance with CIE Publication No. 54.2, Retro-reflection using CIE Standard Illuminant A. Any of the recommended apertures may be used. Measurements shall be taken at the specified observation angle α and entrance angle β . The entrance angle β shall be set by its first component β_1 with the second component $\beta_2 = 0^\circ$, the rotation angle ε shall be $\varepsilon = 0^\circ$ and the orientation angle ω_s shall be $\omega_s = 0^\circ$.

The requirements of minimum coefficient of Retro-reflection R' are specified in the table 27.

Geometry of measurements		Colours								
α	$\beta_1 (\beta_2 = 0^\circ)$	White	Yellow	Red	Green		Blue	Brown		
12'	+ 5°	250	170	45	45		20	12		
	+ 30°	150	100	25	25		11	8.5		
	+ 40°	110	70	15	12		8	5.0		
20'	+ 5°	180	120	25	21		14	8		
	+ 30°	100	70	14	12		8	5		
	+ 40°	95	60	13	11		7	3		
2°	+ 5°	5	3	1	0.5		0.2	0.2		
	+ 30°	2.5	1.5	0.4	0.3		#	#		
	+ 40°	1.5	1.0	0.3	0.2		#	#		

indicates "Value greater than zero but not significant or applicable"

Table 27: Minimum Coefficient of Retroreflection, performance Class R2 Europe (= RA2 in EN 12899-1)

For material processed with process colours, with or without clear overlay film, the minimum value of the coefficient of Retro-reflection shall not be less than 70% of the values specified in the tables. For material processed with red process colour or red overlay film over yellow microprismatic sheeting, the coefficient of Retro-reflection shall not be less than 50% of the values specified in the tables.

3.2.3. Rotational symmetry

When measured according to clause 3.2.2, for the observation angle $\alpha = 0.33^\circ$ and entrance angle $\beta_1 = 5^\circ (\beta_2 = 0^\circ)$, the ratio between the minimum and the maximum coefficient of Retro-reflection when rotating from $\varepsilon - 75^\circ$ to $+ 50^\circ$ in 25° steps, shall not be greater than 2.5.1.

3.2.4. Impact resistance

The test is carried out according to EN 12899-1 using a hard body having a mass of 450 g with a contact radius of 50 mm. The hard body is dropped from a height of 220 mm on a sample that shall be supported over an open area of 100 mm x 100 mm.

3.3. Visibility after accelerated artificial weathering

The apparatus shall be either an air cooled or water cooled Xenon arc weathering device capable of exposing samples in accordance with EN ISO 4892-2: 1994.

Preparation of test specimens should be in accordance with the general guideline given in EN ISO 4892-2: 1994.

The samples shall be exposed in accordance to EN ISO 4892-2: 1994 using the parameters given in the following table 28, for a period of 2000 hours.

Exposure parameters	Air cooled lamp	Water cooled lamp
Light/dark/water spray cycle	Continuous light with water spray on specimens for 18 minutes every 2 hours	Continuous light with water spray on specimens for 18 minutes every 2 hours
Black standard temperature during light only periods	(65 ± 3) °C using a black standard thermometer	(65 ± 3)°C using a black standard thermometer
Relative humidity	(50 ± 5) %	(50 ± 5) %
Irradiance (W/m ²) controlled at		
- over 300-400 nm range	60	60
- over 300-800 nm range	550	630

Table 28: Artificial weathering test parameters

Note 1 – Water used for specimen spray should contain no more than 1 ppm silica. Higher levels of silica may produce spotting on samples and variability in results. Water of the required purity may be obtained by distillation or by a combination of deionisation and reverse osmosis.

Note 2 – Whilst irradiance levels should be set at the above levels, variations in filter ages and transmissivity, and in calibration variations, will be generally mean that irradiance error will be in the order of ± 10%.

After weathering, following test shall be carried out

- day time colour (according to clause 3.2.1)
- Luminance factor (according to clause 3.2.1)

- Coefficient of Retroreflection – (according to clause 3.2.2)

After exposure the coefficient of retro-reflection measured at an observation angle $\alpha = 0.33^\circ$ (or $\alpha = 0.2^\circ$) and entrance angle $\beta_1 = 5^\circ$ and 30° ($\beta_2 = 0^\circ$), shall not be less than 80% of the values required for new material in 3.2.2.

After exposure the chromaticity co-ordinates and Luminance factor measured according to clause 3.2.1, shall comply with the requirements specified in Table 29, as appropriate.

Colour		Chromaticity Coordinates				Luminance Factor β	
		1	2	3	4	Class B1	Class B2
White	x	0.355	0.305	0.285	0.335	≥ 0.27	≥ 0.40
	y	0.355	0.305	0.325	0.375		
Yellow	x	0.545	0.487	0.427	0.465	≥ 0.16	≥ 0.24
	y	0.454	0.423	0.483	0.534		
Red	x	0.735	0.674	0.569	0.655	≥ 0.03	≥ 0.03
	y	0.265	0.236	0.341	0.345		
Green	x	0.007	0.248	0.177	0.026	≥ 0.03	≥ 0.03
	y	0.703	0.409	0.362	0.399		
Brown	x	0.455	0.523	0.479	0.558	0.04 – 0.06	0.03 – 0.09
	y	0.397	0.429	0.373	0.394		
Blue	x	0.078	0.150	0.210	0.137	≥ 0.01	≥ 0.01
	y	0.171	0.220	0.160	0.038		

Table 29 – Permitted colour area in CIE 1931 diagram and Luminance factors for daylight appearance after accelerated weathering test or after outdoor exposure

4. Evaluation of Conformity and CE Marking

4.1 Attestation of conformity system

The system of attestation of conformity is System 1 as described in Council Directive 89/106/EEC. Annex III, Clause 2 "Certification of Conformity of the product by an Approved Body and is detailed as followed:

a) Task of the manufacturer

(1) Factory Production Control (FPC), including further testing of samples taken at the factory by the manufacturer in accordance with the prescribed test plan.

b) Tasks of the approval body

- (2) Initial Type Testing (ITT) of the product
- (3) Initial inspection of the factory and of the Factory Production Control (FPC)
- (4) Continuous surveillance, assessment and approval of the FPC.

4.2 Responsibilities

4.2.1. Task of the manufacturer

4.2.1.1. Factory Production Control (FPC)

The ETA holder has a FPC system in his plants and exercises permanent internal control of the production, including test samples in accordance with his control plan.

The control plan and the provisions taken by the ETA holder for components not produced by him have been agreed with the Approval Body and deposited with UBAtc where it is only made available to Notified Bodies involved in the conformity attestation procedure.

This control plan will be given to the Notified Body chosen by the ETA holder to perform the foreseen tasks on attestation of conformity.

The manufacturer only uses raw materials supplied with the relevant inspection documents as laid down in the control plan. The incoming raw materials are subjected to verifications by the manufacturer before acceptance.

All the elements, requirements and provisions adopted by the manufacturer are documented in a systematic manner in the form of written processes and procedures. This production control system ensures conformity with this ETA.

The results of FPC are recorded and evaluated. The records include:

- Designation of the product, raw materials and components.
- Type of control or testing

- Date of the product's manufacture and date of testing of the product or raw materials and components.
- Results of controls and testing and, if appropriate, comparison with requirements.
- Signature of person responsible for FPC.

The records shall be presented to the inspection body during the continuous surveillance. On request, they shall be presented to UBAtc.

Details of the extent, nature and frequency of testing and controls to be performed with FPC shall correspond to the control plan which is part of the technical documentation of this ETA.

4.2.2 Tasks of the Notified Body.

4.2.2.1 Initial Type Testing (ITT)

For ITT, the results of the test performed as part of the assessment for this ETA shall be used unless there are changes in the production line or plant. In such cases, the necessary new ITT has to be agreed between UBAtc and the Notified Body involved.

4.2.2.2 Initial Inspection of factory and Factory Production Control (FPC)

The Notified Body shall ascertain that, in accordance with the control plan the factory (in particular, employees and equipment) and the FPC are suitable to ensure continuous and orderly manufacturing of the components according to specifications mentioned in clause 2 and 3 of this ETA.

4.2.2.3 Continuous surveillance, assessment and approval of FPC.

The Notified Body should visit the factory at least once a year for surveillance. It has to be verified that the system of FPC and the specified manufacturing process are maintained, taking into account the deposited control plan. Continuous surveillance and assessment of FPC have to be performed in accordance to the control plan.

During each visit, the Notified Body shall utilize an ad-hoc check list and shall examine, among others:

- the control registers of raw materials, products in course of manufacture and finished products.
- The document attesting the respect of the control frequencies.
- The conformity of the products subjected to this ETA.

In cases where the provisions of the ETA and the control plan are no longer fulfilled, the conformity certificate should be withdrawn.

4.3 CE Marking

The CE marking shall be affixed on the product or the packaging or on the transport documents (DDT) accompanying the components of the product. The symbol "CE" shall be followed by identification number of the Notified Body involved and shall be accompanied by the following information:

- Name or identification mark of the ETA holder.
- Legal address of the ETA holder and the manufacturing plants
- The last 2 digits of the year in which the CE marking was affixed.
- The number of the CE certificate of conformity of FPC
- The number of this ETA
- Product identification
- Product Performance referring to this ETA


	<i>"CE"-symbol</i>
nnnn	<i>Number of Notified Body</i>
3M Deutschland GmbH Carl-Schurz-Str. 1 D- 41453 Neuss, Germany	<i>Name and address of the ETA-holder</i>
3M Brownwood, Texas 76801 – US	<i>Manufacturing plant</i>
13	<i>Two last digits of year of affixing CE Marking</i>
nnnn-CPD-XXXX	<i>Number of EC certificate of conformity</i>
ETA N° 13/0304	<i>ETA Number</i>
3M™ High Intensity Prismatic Reflective Sheeting Series 3930	<i>Product identification</i>
Product performances: See ETA 13/0304	<i>Use category related to weather exposure</i> <i>Use category related to intended use</i>

Figure 1: Example of CE-Marking

5. Assumptions under which the fitness of the products for the intended use was favourably assessed.

5.1. Manufacturing

3M High Intensity Prismatic Reflective Sheeting series 3930, combinations with or without 3M Electrocut Film series 1170 or Process Colour Series 4700 or Piezo Inkjet Ink Series 8800 UV, and with or without 3M Dew Resistant Overlay Film 1180 or 3M Premium Protective Overlay Film 1160, shall correspond, as far as their composition and manufacturing process is concerned, to the products subject to the approval tests. A manufacturing process has been deposited with UBAtc.

5.2 Installation

5.2.1 General

It is the responsibility of the ETA holder to guarantee that the information about design and installation of the systems as described in clause 2.1 of this ETA, are effectively communicated to the concerned people. This information can be given using reproductions of the respective parts of this ETA. Besides, all the data concerning the execution shall be indicated clearly on the packaging and or the enclosed instruction sheets using one or several illustrations.

In any case, it is suitable to comply with national regulations and particularly concerning national traffic code.

5.2.2. Design

The substrate used in this ETA is aluminium. Properly prepared aluminium sheets and aluminium extrusions are found to be most reliable. Most clean, smooth, relatively non-porous, flat, rigid, weather resistant surfaces are satisfactory for proper application of High Intensity Prismatic sheeting. Users are urged to carefully evaluate all other substrates for adhesion and sign durability, including impact resistance.

5.2.3. Application

5.2.3.1. 3M High Intensity Prismatic Reflective Sheeting Reflective Sheeting Series 3930

The sheeting must be stored in a cool, dry area, preferably at 18-24°C and 30-50% RH, and should be applied within one year from delivery. Rolls should be stored horizontally in the shipping carton. Partially used rolls should be returned to the shipping carton or suspended horizontally on a rod or pipe through the core.

Unprocessed sheets should be stored flat. Finished signs and applied blanks should be stored on edge. Package for shipment must prevent movement and chafing. Store sign packages indoors on edges. Panels or finished signs must remain dry during shipping and storage. If packaged signs become wet, unpack immediately and allow to dry.

The recognition and preparation of the substrate as well as the generalities about the application of this product series, which is fully described in the current version of the ETA holder catalogue, its technical bulletins and web site www.3M.com/TSS, shall be carried out in compliance with national regulations in effect, if any.

“3M High Intensity Prismatic Reflective Sheeting Reflective Sheeting Series 3930” incorporates a pressure sensitive adhesive and shall be applied to the sign substrate at room temperature (18°C) or higher by any of the following methods : mechanical squeeze roll applicator, hand squeeze roll applicator, hand application. If the heater is needed to warm to the minimum application temperature of 18°C, it must be directed at the substrate only.

Users are urged to carefully evaluate all substrates for adhesion and sign durability. “3M High Intensity Prismatic Reflective Sheeting Series 3930” is designed primarily for application to flat substrates. Sign failures caused by the substrate or improper surface preparation are not the responsibility of the ETA holder.

5.2.3.2. 3M Electrocut film Series 1170

Electrocut film shall be stored in a cool, dry area 18-24°C and 30 – 50 % RH, and shall be used within one year from date of purchase.

These overlay films have a transparent film release liner designed to aid the cutting process and the removal of the film weed after cutting. It is recommended that inside radius corner fonts be used when cutting film. More over the ETA holder recommend the following steps :

- Adjust knife pressure to cut cleanly through the film without cutting into the liner. A 30° blade works best. Spacing between the letters or numbers should be adjusted to the aesthetic preference of the user. Consult the operating manual for instructions on how to regulate spacing. Do not cut at high speed on variable speed machines.
- Avoid sharp bends when cutting and handling film as this may cause film to release from the liner.
- After cutting is complete, lay sheets flat, face to face, back to back. Always store sheets in this manner until the sheeting has been weeded and transfer tape has been applied.
- Use a stripping tool designed for weeding films that has a blunt (not sharp) edge.

- After weeding is complete, store sheets flat, face to face, and back to back, until transfer tape has been applied.
- Transfer tape can be applied either by hand using a plastic squeegee or through a hand squeeze roll laminator. If applying the transfer tape by hand, care must be taken to always squeeze from the centre to the outside in all directions.

Series 1170 film may be applied to the sheeting either before or after the sheeting has been applied to a substrate. The use of hand squeeze roll laminator is recommended to ensure satisfactory results. Use the “split liner method” – Start in the middle of the sheet and remove half the liner to ensure proper alignment.

After Series 1170 film and sheeting have been applied, remove the transfer tape by carefully removing the tape at as low angle as possible

- When the application tape has been removed, re-roll the sign through the laminator to ensure good adhesion. Adequate pressure is a key factor relating to the ultimate strength and durability of the sheeting - to - substrate adhesion.
- A clean cutting blade is required. To remove the adhesive build up use soft cloth dampened with mineral spirits, isopropyl alcohol or 3M Natural Cleaner.

5.2.3.3. 3M Process Colour Series 4700

For screen processing, the equipment and set-up are the following: proper colour and durability is achieved by using a high grade polyester, monofilament screen fabric mesh size P.E. 157. Other size screen fabrics do not produce satisfactory colour and durability. Screen printing should be accomplished using the off-contact screening method. Direct contact screen printing should not be used. Be sure that screens, sheeting, plus screening and drying areas are dust, dirt and lint free.

For the mixing and thinning, it is important that the colours and sheeting be brought to normal ambient room temperature and humidity of the screen printing area before processing. Thin sparingly using 3M Thinner of the same series as the process colours. Do not use extenders, drying agents, or other materials as they will adversely affect performance life.

Air Drying: processed sheeting for air drying must be placed on open racks to allow adequate air circulation. High volume fans must be directed through the racks. Drying times will be increased by high humidity, low temperature, poor air circulation, heavy colour coat, and excessive thinning. Addition of drying agents is not recommended. Processed sheetings must be air dried for a minimum of 3 hours per colour.

Oven drying: Processed sheeting for oven drying must be placed on open racks individually with sufficient open space for unobstructed air flow.

All inks should not be stored at elevated temperatures and must be used within one year after the date of purchase or within the indicated shelf life.

5.2.3.4. 3M Piezo Inkjet Ink Series 8800 UV

3M Piezo Ink Jet Ink Series 8800UV is designed as part of the 3M MCS™ (Matched Component System) for application using the Durst Rho 161TS / 162TS Printer onto 3M High Intensity Prismatic Reflective Sheeting Series 3930 BEFORE mounting the sheeting onto a sign substrate. These UV-curable inks are durable, weather-resistant, and have excellent colour retention when used in combination with 3M ElectroCut™ Film 1170 or 3M Dew Resistant Overlay Film 1180 or 3M Premium Protective Overlay Film 1160 as an overlamine.

Detailed printing guidelines in order to achieve traffic sign colours according to this ETA can be obtained in the latest Product Bulletin for 3M Piezo Ink Jet Ink Series 8800UV.

Above mentioned overlaminates must always be applied, following below instructions:

To avoid a silvering artifact (trapped air between ink layer and overlamine), the lamination process should be conducted under a controlled set of conditions.

Recommended laminator specifications and set-up:

- Roll diameter: max. 350 mm; Roll weight: approximately 80 kg; Roll width: 1400-1600 mm
- Core size: 3 inches; 2 Take-up shafts; 2 Supply shafts
- Heatable top roller: min. 45°C; Pressure: > 8 bar

3M Piezo Ink Jet Ink Series 8800UV should not be stored at elevated temperatures. It must be used within the indicated shelf life.

5.2.3.5. Protective Overlay Films: 3M Dew Resistant Overlay Film 1180 and 3M Premium Protective Overlay Film 1160

Protective Overlay film shall be stored in a cool, dry area at 18-24°C and 30 – 50 % RH, and shall be used within one year from date of purchase.

The application of any Protective Overlay Film is typically done on the finished signface (after the application of the ECF and ink) but PRIOR to the application of frames or sign assembly. The Protective Overlay Film must be applied using a squeeze roll applicator (see 3M Information Folder IF1.13). The split liner method may be used.

3M Dew Resistant Overlay Film Series 1180 provides a very sensitive active layer that is prone to contamination and scratches. This active layer is therefore protected by a water-soluble, clear protective coating. This protective coating should remain on the sign as long as possible. Ideally it should be removed after the traffic sign is erected. If the protective coating is removed before sign erection, precautions have to be taken to prevent any contamination or mechanical damage. Due to the protective coating, it is strongly recommended NOT to overlap the Dew Resistant Overlay Film.

Annex 1: Use Options

VISIBILITY		USE OPTIONS												
		Option 1	Option 2	Option 3	Option 4	Option 5	Option 6	Option 7	Option 8	Option 9	Option 10	Option 11	Option 12	
Daytime Colour		Tm 4.4.2.1 Lv 5.4.1	Tm 4.4.2.1 Lv 5.4.1	Tm 4.4.2.1 Lv 5.4.1	Tm 4.4.2.1 Lv 5.4.1	Tm 4.4.2.1 Lv 5.4.1	Tm 4.4.2.1 Lv 5.4.1	Tm 4.4.2.1 Lv 5.4.1	Tm 4.4.2.1 Lv 5.4.1	Tm 4.4.2.1 Lv 5.4.1	Tm 4.4.2.1 Lv 5.4.1	Tm 4.4.2.1 Lv 5.4.1	Tm 4.4.2.1 Lv 5.4.1	
Luminance factor		Tm 4.4.2.1 Lv 5.4.1	Tm 4.4.2.1 Lv 5.4.1	Tm 4.4.2.1 Lv 5.4.1	Tm 4.4.2.1 Lv 5.4.1	Tm 4.4.2.1 Lv 5.4.1	Tm 4.4.2.1 Lv 5.4.1	Tm 4.4.2.1 Lv 5.4.1	Tm 4.4.2.1 Lv 5.4.1	Tm 4.4.2.1 Lv 5.4.1	Tm 4.4.2.1 Lv 5.4.1	Tm 4.4.2.1 Lv 5.4.1	Tm 4.4.2.1 Lv 5.4.1	
Fluorescence Luminance factor		NOT TO BE TESTED	NOT TO BE TESTED	Tm 4.4.2.2 Lv 5.4.2	NOT TO BE TESTED	Tm 4.4.2.2 Lv 5.4.2	NOT TO BE TESTED	NOT TO BE TESTED	Tm 4.4.2.2 Lv 5.4.2	NOT TO BE TESTED	NOT TO BE TESTED	NOT TO BE TESTED	NOT TO BE TESTED	
Night-time colour		NOT TO BE TESTED	Tm 4.4.2.3 Lv 5.4.3	Tm 4.4.2.3 Lv 5.4.3	Tm 4.4.2.3 Lv 5.4.3	Tm 4.4.2.3 Lv 5.4.3	Tm 4.4.2.3 Lv 5.4.3	NOT TO BE TESTED	NOT TO BE TESTED	NOT TO BE TESTED	NOT TO BE TESTED	NOT TO BE TESTED	NOT TO BE TESTED	
Coefficient of Retro-reflection-Case A or Case B		Tm 4.4.2.4 Lv 5.4.4	Tm 4.4.2.4 Lv 5.4.4	Tm 4.4.2.4 Lv 5.4.4	Tm 4.4.2.4 Lv 5.4.4	Tm 4.4.2.4 Lv 5.4.4	Tm 4.4.2.4 Lv 5.4.4	Tm 4.4.2.4 Lv 5.4.4	Tm 4.4.2.4 Lv 5.4.4	Tm 4.4.2.4 Lv 5.4.4	Tm 4.4.2.4 Lv 5.4.4	Tm 4.4.2.4 Lv 5.4.4	Tm 4.4.2.4 Lv 5.4.4	
Colour Contrast Factors		NOT TO BE TESTED	Tm 4.4.2.5 Lv 5.4.5	NOT TO BE TESTED	Tm 4.4.2.5 Lv 5.4.5	NOT TO BE TESTED	Tm 4.4.2.5 Lv 5.4.5	Tm 4.4.2.5 Lv 5.4.5	NOT TO BE TESTED	Tm 4.4.2.5 Lv 5.4.5	NOT TO BE TESTED	NOT TO BE TESTED	NOT TO BE TESTED	
Total luminous transmittance		NOT TO BE TESTED	NOT TO BE TESTED	NOT TO BE TESTED	Tm 4.4.2.6 Lv 5.4.6	NOT TO BE TESTED	Tm 4.4.2.6 Lv 5.4.6	NOT TO BE TESTED	NOT TO BE TESTED	Tm 4.4.2.6 Lv 5.4.6	NOT TO BE TESTED	NOT TO BE TESTED	NOT TO BE TESTED	
Impact resistance		Tm 4.4.2.7 Lv 5.4.7	Tm 4.4.2.7 Lv 5.4.7	Tm 4.4.2.7 Lv 5.4.7	Tm 4.4.2.7 Lv 5.4.7	Tm 4.4.2.7 Lv 5.4.7	Tm 4.4.2.7 Lv 5.4.7	Tm 4.4.2.7 Lv 5.4.7	Tm 4.4.2.7 Lv 5.4.7	Tm 4.4.2.7 Lv 5.4.7	Tm 4.4.2.7 Lv 5.4.7	Tm 4.4.2.7 Lv 5.4.7	NOT TO BE TESTED	
DURABILITY														
Temperature resistance		NOT TO BE TESTED	Tm 4.7.1 Lv 5.7.1	Tm 4.7.1 Lv 5.7.1	Tm 4.7.1 Lv 5.7.1	NOT TO BE TESTED	NOT TO BE TESTED	Tm 4.7.1 Lv 5.7.1	Tm 4.7.1 Lv 5.7.1	Tm 4.7.1 Lv 5.7.1	Tm 4.7.1 Lv 5.7.1	Tm 4.7.1 Lv 5.7.1	NOT TO BE TESTED	
Visibility after accelerated weathering test	Day-time colour (*)	Tm 4.7.2 + 4.4.2.1 Lv 5.7.2	Tm 4.7.2 + 4.4.2.1 Lv 5.7.2	Tm 4.7.2 + 4.4.2.1 Lv 5.7.2	Tm 4.7.2 + 4.4.2.1 Lv 5.7.2	Tm 4.7.2 + 4.4.2.1 Lv 5.7.2	Tm 4.7.2 + 4.4.2.1 Lv 5.7.2	Tm 4.7.2 + 4.4.2.1 Lv 5.7.2	Tm 4.7.2 + 4.4.2.1 Lv 5.7.2	Tm 4.7.2 + 4.4.2.1 Lv 5.7.2	Tm 4.7.2 + 4.4.2.1 Lv 5.7.2	Tm 4.7.2 + 4.4.2.1 Lv 5.7.2	Tm 4.7.2 + 4.4.2.1 Lv 5.7.2	
	Luminance factor (*)	Tm 4.7.2 + 4.4.2.1 Lv 5.7.2	Tm 4.7.2 + 4.4.2.1 Lv 5.7.2	Tm 4.7.2 + 4.4.2.1 Lv 5.7.2	Tm 4.7.2 + 4.4.2.1 Lv 5.7.2	Tm 4.7.2 + 4.4.2.1 Lv 5.7.2	Tm 4.7.2 + 4.4.2.1 Lv 5.7.2	Tm 4.7.2 + 4.4.2.1 Lv 5.7.2	Tm 4.7.2 + 4.4.2.1 Lv 5.7.2	Tm 4.7.2 + 4.4.2.1 Lv 5.7.2	Tm 4.7.2 + 4.4.2.1 Lv 5.7.2	Tm 4.7.2 + 4.4.2.1 Lv 5.7.2	Tm 4.7.2 + 4.4.2.1 Lv 5.7.2	
	Fluorescence Luminance factor (*)	NOT TO BE TESTED	NOT TO BE TESTED	Tm 4.7.2 + 4.4.2.2 Lv 5.7.3	NOT TO BE TESTED	Tm 4.7.2 + 4.4.2.2 Lv 5.7.3	NOT TO BE TESTED	NOT TO BE TESTED	NOT TO BE TESTED	4.7.2 + 4.4.2.2 Lv 5.7.3	NOT TO BE TESTED	NOT TO BE TESTED	NOT TO BE TESTED	NOT TO BE TESTED
	Coefficient of Retro-reflection (*)	Tm 4.7.2 + 4.4.2.4 Lv 5.7.4	Tm 4.7.2 + 4.4.2.4 Lv 5.7.4	Tm 4.7.2 + 4.4.2.4 Lv 5.7.4	Tm 4.7.2 + 4.4.2.4 Lv 5.7.4	Tm 4.7.2 + 4.4.2.4 Lv 5.7.4	Tm 4.7.2 + 4.4.2.4 Lv 5.7.4	Tm 4.7.2 + 4.4.2.4 Lv 5.7.4	Tm 4.7.2 + 4.4.2.4 Lv 5.7.4	Tm 4.7.2 + 4.4.2.4 Lv 5.7.4	Tm 4.7.2 + 4.4.2.4 Lv 5.7.4	Tm 4.7.2 + 4.4.2.4 Lv 5.7.4	Tm 4.7.2 + 4.4.2.4 Lv 5.7.4	Tm 4.7.2 + 4.4.2.4 Lv 5.7.4
Visibility after outdoor exposure	Day-time colour	Tm 4.7.3 + 4.4.2.1 Lv 5.7.2	Tm 4.7.3 + 4.4.2.1 Lv 5.7.2	Tm 4.7.3 + 4.4.2.1 Lv 5.7.2	Tm 4.7.3 + 4.4.2.1 Lv 5.7.2	Tm 4.7.3 + 4.4.2.1 Lv 5.7.2	Tm 4.7.3 + 4.4.2.1 Lv 5.7.2	Tm 4.7.3 + 4.4.2.1 Lv 5.7.2	Tm 4.7.3 + 4.4.2.1 Lv 5.7.2	Tm 4.7.3 + 4.4.2.1 Lv 5.7.2	Tm 4.7.3 + 4.4.2.1 Lv 5.7.2	Tm 4.7.3 + 4.4.2.1 Lv 5.7.2	Tm 4.7.3 + 4.4.2.1 Lv 5.7.2	
	Luminance factor	Tm 4.7.3 + 4.4.2.1 Lv 5.7.2	Tm 4.7.3 + 4.4.2.1 Lv 5.7.2	Tm 4.7.3 + 4.4.2.1 Lv 5.7.2	Tm 4.7.3 + 4.4.2.1 Lv 5.7.2	Tm 4.7.3 + 4.4.2.1 Lv 5.7.2	Tm 4.7.3 + 4.4.2.1 Lv 5.7.2	Tm 4.7.3 + 4.4.2.1 Lv 5.7.2	Tm 4.7.3 + 4.4.2.1 Lv 5.7.2	Tm 4.7.3 + 4.4.2.1 Lv 5.7.2	Tm 4.7.3 + 4.4.2.1 Lv 5.7.2	Tm 4.7.3 + 4.4.2.1 Lv 5.7.2	Tm 4.7.3 + 4.4.2.1 Lv 5.7.2	
	Coefficient of Retro-reflection	Tm 4.7.3 + 4.4.2.1 Lv 5.7.2	Tm 4.7.3 + 4.4.2.4 Lv 5.7.4	Tm 4.7.3 + 4.4.2.4 Lv 5.7.4	Tm 4.7.3 + 4.4.2.4 Lv 5.7.4	Tm 4.7.3 + 4.4.2.4 Lv 5.7.4	Tm 4.7.3 + 4.4.2.4 Lv 5.7.4	Tm 4.7.3 + 4.4.2.4 Lv 5.7.4	Tm 4.7.3 + 4.4.2.4 Lv 5.7.4	Tm 4.7.3 + 4.4.2.4 Lv 5.7.4	Tm 4.7.3 + 4.4.2.4 Lv 5.7.4	Tm 4.7.3 + 4.4.2.4 Lv 5.7.4	Tm 4.7.3 + 4.4.2.4 Lv 5.7.4	
	Fluorescence Luminance factor	NOT TO BE TESTED	NOT TO BE TESTED	Tm 4.7.3 + 4.4.2.2 Lv 5.7.3	NOT TO BE TESTED	Tm 4.7.3 + 4.4.2.2 Lv 5.7.3	NOT TO BE TESTED	NOT TO BE TESTED	NOT TO BE TESTED	Tm 4.7.3 + 4.4.2.2 Lv 5.7.3	NOT TO BE TESTED	NOT TO BE TESTED	NOT TO BE TESTED	NOT TO BE TESTED

Tm = Test method

Lv = Limit values

(*) = The tests after accelerated exposure can be carried out for the first issue of the ETA in order not to delay the issuing process. In case of further issue of the ETA, then these tests shall be carried out after the outdoor exposure.

Table 1 – Use options

Note: The assessment of the product is performed according to the content of the Option chosen by the manufacturer. Details concerning the characteristics foreseen by the chosen Option as well as test results will be included in an Annex of the ETA.